



THE ANDHRA PETROCHEMICALS LIMITED, VIZAG-530014

Iso Butanol

Technical Data Sheet

1	Formula	$C_4H_{10}O$	
2	CAS Registry Numbers	78-83-1	
3	Molecular Weight	74.1	
4	Product Specifications		Test Method
	1	Purity, wt. %, min.	99
	2	Acidity as acetic acid, wt. %, max.	IS 323 – 1959
	3	Water, wt. %, max.	IS 2362 -1963
	4	Color, APHA, max.	IS 4161 -1967
5	Description	Iso Butanol is a clear, mobile, neutral liquid with a characteristic odor. It is miscible with all common solvents but is only sparingly soluble in water.	
6	Typical and Physical Properties	Distillation range, $^{\circ}C$, 1 atm	106 – 108
		Specific gravity @ 20/20 $^{\circ}C$	0.802 – 0.804
		Non-volatiles, wt. %, max.	0.01
		Appearance	Clear & Colorless
7	Packaging	Available in bulk & barrels.	
8	Safety	Iso Butanol may irritate the skin and eyes. Inhalation of vapors or mists may irritate the respiratory tract and may cause a narcotic effect. Always refer to the Material Safety Data Sheet (MSDS) for detailed information on safety.	
9	Shelf life	a) Unopened barrels:	24 months.
		b) Opened barrels:	6 months
		b) Closed tanks:	Six months under Nitrogen blanketing.
10	Storage and Handling	Iso Butanol can be stored in tanks of normal carbon steel. In this case, however, steps must be taken to exclude moisture from the atmosphere to avoid impairment or product quality (increase moisture content and discoloration by rust). Stainless steel is recommended for more severe storage conditions. Moisture in the atmosphere must be excluded by storing the product under a blanket of inert gas like Nitrogen.	



Iso Butanol

Technical Data Sheet

		<p>Iso Butanol can corrode Aluminum above 60 °C; therefore, it is only possible to use tanks made of aluminum or its alloys at lower temperatures. Drums containing the product should be kept tightly closed in a well-ventilated place.</p> <p>Always refer to the Material Safety Data Sheet (MSDS) for detailed information on handling and disposal.</p>
11	Applications	<p>Iso Butanol is an excellent solvent for acid-curable lacquers and baking finishes derived from urea, melamine, or phenolic resins.</p> <p>When added even in small proportions to alkyl resin paints Iso Butanol reduces the viscosity and thus improves the brush ability and flow.</p> <p>The applications in which Iso Butanol can be used are as follows:</p> <ul style="list-style-type: none">• Solvent for printing inks ,• Extractant in the production of drugs and natural substances ,• Additive in polishes and cleaners ,• Solubilizer in the textile industry (additive in spinning baths or carrier for coloring plastics) ,• Additive in deicing fluids• Anti-icing additive in gasoline• Humectant for cellulose nitrate• Dehydrating agent (entrainer in azeotropic distillation)• Feedstock in the production of glycol ethers• Feedstock for the production of isobutyl acrylate• Feedstock in the production of flotation aids (isobutyl zanthate)• Starting material for the production of wear inhibitors and anti-corrosion additives in engine oils (e.g., zinc diisobutyl dithiophosphate) .

IMPORTANT:

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use.